

**60 µm selfadhesive label foil white
with inbuilt non-permanent glue layer
based on synthetic-rubber!**

FOLIO

**TACKLITE S&G 4.1 LABEL-FILM
S/N 8940**

Spezifikation:

Raw Material	BOPP-Multilayer Cast			
Backside Treatment	EVA-Treatment			
Film Thickness	60µ			
Releaseliner (PET)	30µ			
Total Media Thickness	116µ incl Glue-Coating			
Operating Temperature	15°C bis 45°C			
Opacity	98%			
Wheight	normal 104g/m ² / min. 89 / max. 119g/m ² (ISO 536)			
Whiteness Nominal	L 90,5 / a-1,0 / b-1,8 (ISO 13655)			
Requirement	Val.	Limit	Unit	Method
Flatness	0	±25	mm	NOPAR-CAQ-PA40.doc
Bending Stiffness MD	55	±20	mN	ISO 2493-1, 15°, 10mm
Bending Stiffness CD	70	±20	mN	ISO 2493-1, 15°, 10mm
Release Force	6	± 3	cN/50mm	FTM 3
Peel Adhesion (24h, V2A)	4,8	± 2	N/25mm	FTM 1
Shelf Life	at least 2 Years after Delivery			
Storage Conditions	10 - 30°C, 20 - 70% relative humidity			



TACKLITE S&G 4.1 LABEL-FILM is developed from the combination of an environmentally compatible polypropylene medium which is made up of a Multilayer BOPP-extruded polyolefin-based foil with synthetic rubber and a PET Releaseliner.

It is an adhesive-foil, which sticks long-lasting on all smooth surfaces, because of a special adhesive. This adhesive, based on a synthese rubber, allows the user to stick TACKLITE S&G 4.1 LABEL-FILM on all smooth surfaces and to remove it without any residue on the surface.

We guarantee no pieces or remains of glue on the surface.

TACKLITE S&G 4.1 LABEL-FILM is printable with the current industrial printing technology. Quantities and formats on request.

Applications:

TACKLITE S&G 4.1 LABEL-FILM is suitable for short- and medium-term applications on all smooth surfaces perfectly, because of the special adherent layer (e.g. window pane, vehicles, metall fronts and many more). TACKLITE S&G 4.1 LABEL-FILM can be removed without residue in no time and it still sticks permanent.

Safety instructions:

Don't stick it on soft-PVC, because that compound will stick steady. If used on copper or shiny aluminium surfaces, we suggest to clean it afterwards with acetone

If possible, please test the printability of your systems before you start.

The backside is printed in silver-grey to increase the opacity and an excellent colour gammut!

TACKLITE S&G 4.1 LABEL-Film is a development by NOPAR International GmbH, Bremen.

The Medium is printable with all current printing techniques, like Flex-, HD-Flexo, Roll-Offset and Roto Gravure Printing. Custom-made productions for digital print are also possible.



NOPAR International GmbH
Ladestrasse 3-3a
28197 Bremen/Germany
Phone: +49 421 5208146 0
Fax: +49 421 5208146 9
Mail: info@nopar-international.com
Web: www.nopar-international.com

Please note that all information supplied is correct to date of print, information. It can change without prior notification. This information does not release the manufacturer from his obligation with regard to proper application and handling of the product. All content is based on available technical knowledge at the time of publication.

Released in July 2018

Any reproduction or use of this publication or partially reproduced information in electronic or printed form is prohibited without written Permission and acknowledgment by the owner NOPAR International GmbH