

76 μ m selfadhesive label foil transparent with inbuilt non-permanent glue layer based on synthetic-rubber!

FOLIO

TACKLITE S&G 4.3 OFFSET-MEDIA S/N 8951

Spezifikation:

Raw Material	BOPP-Multilayer Cast			
Backside Treatment	EVA-Treatment			
Film Thickness	76 μ			
Releaseliner (PET)	106 μ			
Total Media Thickness	182 μ incl Glue-Coating			
Operating Temperature	15°C bis 45°C			
Opacity	Window-Clear			
Wheight	normal 217g/m ² / min.202 / max. 232g/m ² (ISO 536)			
Whiteness Nominal	n.a.			
Requirement	Val.	Limit	Unit	Method
Flatness	0	\pm 20	mm	NOPAR-CAQ-PA40.doc
Bending Stiffness MD	346	\pm 40	mN	ISO 2493-1, 15°, 10mm
Bending Stiffness CD	349	\pm 40	mN	ISO 2493-1, 15°, 10mm
Release Force	25	\pm 7	cN/50mm	FTM 3
Peel Adhesion (24h, V2A)	4,8	\pm 2	N/25mm	FTM 1
Shelf Life	at least 2 Years after Delivery			
Storage Conditions	15 - 30°C, 35 - 65% relative humidity			



TACKLITE® S&G 4.3 OFFSET-MEDIA

Developed from the combination of an environmentally compatible polypropylene medium which is made up of a Multilayer BOPP-extruded polyolefin-based foil with synthetic rubber and a PET-Releaseliner. It is an adhesive-foil, which sticks long-lasting on all smooth surfaces, because of a special adhesive. This adhesive, based on a synthese rubber, allows the user to stick FOLIO TACKLITE on all smooth surfaces and to remove it without any residue on the surface.

We guarantee no pieces or remains of glue on the surface.

TACKLITE® S&G 4.3 OFFSET-MEDIA is printable with the current Offset-Printers. Quantities and formats on request.

Applications:

TACKLITE® S&G 4.3 OFFSET-MEDIA is suitable for short- and medium-term applications on all smooth surfaces perfectly, because of the special adherent layer (e.g. window pane, vehicles, metall fronts and many more). TACKLITE can be removed without residue in no time and it still sticks permanent.

Safety instructions:

Don't stick it on soft-PVC, because that compound will stick steady. If used on copper or shiny aluminium surfaces, we suggest to clean it afterwards with acetone

If possible, please test the printability of your systems before you start.

TACKLITE® S&G 4.3 OFFSET-MEDIA is a development by NOPAR International GmbH Bremen.

The Medium is printable with all current Offset-Printers.



Any reproduction or use of this publication or partially reproduced information in electronic or printed form is prohibited without written permission and acknowledgment by the owner
NOPAR International GmbH

Please note that all information supplied is correct to date of print, information. It can change without prior notification. This information does not release the manufacturer from his obligation with regard to proper application and handling of the product. All content is based on available technical knowledge at the time of publication.
Released in February 2024

NOPAR
INTERNATIONAL

Simply iNnovate

NOPAR International GmbH
Dortmunder Straße 32
28199 Bremen/Germany
Phone: +49 421 5208146 0
Fax: +49 421 5208146 9
Mail: info@nopar-international.com
Web: http://www.nopar-international.com